DART AEROSPACE LTD		Work Order:	
	e ⁱ		
Description: Support	7.	Part Number:	D5355-1
Inspection Dwg: D5355	Rev: C		Page 1 of 1

INSPECTION SHEET

0.204 +0.0030 0.204 +/-0.010 0.274 +/-0.010 0.31 +/-0.030 0.20 +/-0.030 0.33 +/-0.030 10° +/-0.5° R0.13 +/-0.030 20° +/-0.5° R0.20 +/-0.030 0.56 +/-0.030 0.21 +/-0.030 0.21 +/-0.030 0.21 +/-0.030 0.13 +/-0.030 0.13 +/-0.030 0.13 +/-0.030 0.13 +/-0.030 R0.29 +/-0.030 0.15 +/-0.030 0.15 +/-0.030 0.15 +/-0.030 0.15 +/-0.030 0.10 +/-0.030 0.11 +/-0.030 0.12 +/-0.030 0.15 +/-0.030 0.50 +/-0.030 0.500 +/-0.030 0.500 +/-0.030 0.500 +/-0.030 0.501 +/-0.030 0.502 +/-0.030 0.503 +/-0.030 0.504 +/-0.030 0.505 +/-0.030 0.255 +/-0.030 0.250 +/-0.030 0	Drawing Dimension	Tolerance	Actual Dimension	Accept	Reject	Method of Inspection	Comments
\$\textit{\te	1.00	+/-0.030					
0.22	0.50	+/-0.030					
0.22	Ø0.204			4			
0.204							e ·
0.274							
0.31	0.274			1			4
0.20	0.31			<u> </u>			1
0.33						,	
10°							
R0.13						y	
20° +/-0.5° R0.20 +/-0.030 0.56 +/-0.030 0.40 +/-0.030 0.21 +/-0.030 R0.40 +/-0.030 0.13 +/-0.030 R0.29 +/-0.030 0.15 +/-0.030 1.28 +/-0.030 1.28 +/-0.030 R0.25 +/-0.030 1.200 +/-0.010 2.00 +/-0.030 0.40 +/-0.030 0.50 +/-0.030 0.500 +/-0.030 0.501 +/-0.030 0.502 +/-0.030 0.503 +/-0.030 0.504 +/-0.030 0.505 +/-0.030 0.501 +/-0.030 0.502 +/-0.030 0.30 +/-0.030 0.30 +/-0.030 0.25 +/-0.030 0.150 +0.015/-0.000 0.250 +/-0.015 R0.13 +/-0.030 0.65 +/-0.030	R0.13						
R0.20			140			192	
0.56	R0.20				1		-7
0.40	0.56		1.5				
0.21 +/-0.030 R0.40 +/-0.030 0.13 +/-0.030 R0.29 +/-0.030 0.15 +/-0.030 1.28 +/-0.030 0.13 +/-0.030 R0.25 +/-0.030 1.200 +/-0.010 2.00 +/-0.030 0.50 +/-0.030 0.50 +/-0.030 0.500 +/-0.010 Ø0.257 +0.006/-0.001 5.01 +/-0.030 R0.30 +/-0.030 0.30 +/-0.030 0.25 +/-0.030 R0.13 +/-0.030 0.250 +/-0.015 R0.13 +/-0.030 0.65 +/-0.030				7,			
R0.40							¥.
0.13 +/-0.030 R0.29 +/-0.030 0.15 +/-0.030 1.28 +/-0.030 0.13 +/-0.030 R0.25 +/-0.030 1.200 +/-0.010 2.00 +/-0.030 0.40 +/-0.030 0.50 +/-0.030 0.50 +/-0.010 Ø0.257 +0.006/-0.001 5.01 +/-0.030 R0.30 +/-0.030 0.30 +/-0.030 0.25 +/-0.030 R0.13 +/-0.030 0.250 +/-0.015 R0.13 +/-0.030 0.65 +/-0.030				in .			**** **** ***** *****
R0.29	0.13			-			
0.15 +/-0.030 1.28 +/-0.030 0.13 +/-0.030 R0.25 +/-0.030 1.200 +/-0.010 2.00 +/-0.030 0.40 +/-0.030 0.50 +/-0.030 0.500 +/-0.010 Ø0.257 +0.006/-0.001 5.01 +/-0.030 R0.30 +/-0.030 0.30 +/-0.030 R0.13 +/-0.030 0.250 +/-0.030 0.250 +/-0.015/-0.000 0.250 +/-0.015 R0.13 +/-0.030 0.65 +/-0.030			100				
1.28 +/-0.030 0.13 +/-0.030 R0.25 +/-0.030 1.200 +/-0.010 2.00 +/-0.030 0.40 +/-0.030 0.50 +/-0.030 0.500 +/-0.010 Ø0.257 +0.006/-0.001 5.01 +/-0.030 R0.30 +/-0.030 0.30 +/-0.030 0.25 +/-0.030 R0.13 +/-0.030 0.150 +0.015/-0.000 0.250 +/-0.015 R0.13 +/-0.030 0.250 +/-0.015 R0.13 +/-0.030 0.65 +/-0.030	0.15						
0.13 +/-0.030 R0.25 +/-0.010 1.200 +/-0.030 0.40 +/-0.030 0.50 +/-0.030 0.500 +/-0.010 Ø0.257 +0.006/-0.001 5.01 +/-0.030 R0.30 +/-0.030 0.30 +/-0.030 0.25 +/-0.030 R0.13 +/-0.030 0.150 +0.015/-0.000 0.250 +/-0.015 R0.13 +/-0.030 0.250 +/-0.015 R0.13 +/-0.030 0.65 +/-0.030	1.28						
R0.25						4	
1.200					,	1.0	
2.00	1.200					·	
0.40 +/-0.030 0.50 +/-0.030 0.500 +/-0.010 Ø0.257 +0.006/-0.001 5.01 +/-0.030 R0.30 +/-0.030 0.30 +/-0.030 0.25 +/-0.030 R0.13 +/-0.030 0.150 +0.015/-0.000 0.250 +/-0.015 R0.13 +/-0.030 0.65 +/-0.030	2.00					100	
0.500 +/-0.010 Ø0.257 +0.006/-0.001 5.01 +/-0.030 R0.30 +/-0.030 0.30 +/-0.030 0.25 +/-0.030 R0.13 +/-0.030 0.150 +0.015/-0.000 0.250 +/-0.015 R0.13 +/-0.030 0.65 +/-0.030	0.40						
0.500 +/-0.010 Ø0.257 +0.006/-0.001 5.01 +/-0.030 R0.30 +/-0.030 0.30 +/-0.030 0.25 +/-0.030 R0.13 +/-0.030 0.150 +0.015/-0.000 0.250 +/-0.015 R0.13 +/-0.030 0.65 +/-0.030	0.50	+/-0.030					74 · · · · · · · · · · · · · · · · · · ·
Ø0.257 +0.006/-0.001 5.01 +/-0.030 R0.30 +/-0.030 0.30 +/-0.030 0.25 +/-0.030 R0.13 +/-0.030 0.150 +0.015/-0.000 0.250 +/-0.015 R0.13 +/-0.030 0.65 +/-0.030	0.500				4.7		
R0.30 +/-0.030	Ø0.257				1 4	18 10 10	ž s s
R0.30 +/-0.030	5.01					1 1 N	*.
0.30 +/-0.030 0.25 +/-0.030 R0.13 +/-0.030 0.150 +0.015/-0.000 0.250 +/-0.015 R0.13 +/-0.030 0.65 +/-0.030							
0.25 +/-0.030 R0.13 +/-0.030 0.150 +0.015/-0.000 0.250 +/-0.015 R0.13 +/-0.030 0.65 +/-0.030							
R0.13 +/-0.030 0.150 +0.015/-0.000 0.250 +/-0.015 R0.13 +/-0.030 0.65 +/-0.030							
0.150 +0.015/-0.000 0.250 +/-0.015 R0.13 +/-0.030 0.65 +/-0.030							
0.250 +/-0.015 R0.13 +/-0.030 0.65 +/-0.030					101		
R0.13 +/-0.030 0.65 +/-0.030			an and	1.6			:
0.65 +/-0.030					4		
			-				
	Moseurod by:		Observation	.		00.1	

Measured by:	Checked by:	QC Inspector:	
Date:	Date:	Date:	
Engineering Approval			

Engineering Approval: (If necessary)	Date:				
Rev Date Change		Davised by	Annround		

Rev	Date	Change	Revised by Approved
Α	18.06.12	New Issue	MG/KJ 😽
			7/ 1